

MICRO SE 3.0-08

*Image is for illustrative purposes only

Screw compressor with belt transmission, compact and silent.

Three-phase lubricated screw compressor with belt transmission with electromechanical control and direct starter. Soundproof cab in hot-dip galvanised sheet metal for maximum silence


TECHNICAL DATA

| | | |
|---------------------------------|----------------------|------|
| Product code | V51JS72FNM760 | |
| Lubrication | Lubricated | |
| Air-end | FS14 | |
| Power | 3 | |
| Air outflow | l/min. | 430 |
| | m ³ /min. | 0,43 |
| | c.f.m. | 15 |
| Max. pressure | bar | 8 |
| | p.s.i. | 116 |
| Nr. of stages | 1 | |
| Sound level (dB(A)) | 59 | |
| Voltage / Frequency (Volt / Hz) | 400/50 | |
| Connection (G) | 1/2" | |
| Controller | Login | |
| Type motor | Electric | |
| Energy efficiency | IE3 | |
| Gross weight (kg) | 110 | |
| Net weight (kg) | 99 | |
| Packaging dimensions LxWxH (mm) | 720x670x970 | |
| Net Dimensions LxWxH (mm) | 580x480x760 | |

*Sound pressure level measurement carried out at a distance of 7 metres.