

**MICRO SE 4.0-10-200**

\*Image is for illustrative purposes only

Screw compressor with belt transmission, complete with tank.

Three-phase lubricated screw compressor with belt transmission with electromechanical control and direct starter. Soundproof cab made of hot-painted sheet metal and complete with 200-litre tank


**TECHNICAL DATA**

|                                 |                      |      |
|---------------------------------|----------------------|------|
| Product code                    | V77JP72FNM701        |      |
| Lubrication                     | Lubricated           |      |
| Air-end                         | FS14                 |      |
| Air receiver (l)                | 200                  |      |
| Power                           | 4                    |      |
| Air outflow                     | l/min.               | 485  |
|                                 | m <sup>3</sup> /min. | 0,49 |
|                                 | c.f.m.               | 17   |
| Max. pressure                   | bar                  | 10   |
|                                 | p.s.i.               | 145  |
| Nr. of stages                   | 1                    |      |
| Sound level (dB(A))             | 60                   |      |
| Voltage / Frequency (Volt / Hz) | 400/50               |      |
| Connection (G)                  | 1/2"                 |      |
| Controller                      | Login                |      |
| Type motor                      | Electric             |      |
| Energy efficiency               | IE3                  |      |
| Gross weight (kg)               | 190                  |      |
| Net weight (kg)                 | 157                  |      |
| Packaging dimensions LxWxH (mm) | 1560x660x1430        |      |
| Net Dimensions LxWxH (mm)       | 1480x520x1280        |      |

\*Sound pressure level measurement carried out at a distance of 7 metres.