

MICRO 4.0-08-200

\*Image is for illustrative purposes only

Screw compressor with belt transmission, complete with tank.

Three-phase belt-transmission lubricated screw compressor with ETMII electronic controller and star/delta starter. Soundproof cab made of painted sheet metal and complete with 200-litre tank



TECHNICAL DATA

Product code	V77JR92FNMA01	
Lubrication	Lubricated	
Air-end	FS14	
Air receiver (l)	200	
Power	4	
Air outflow	l/min.	580
	m3/min.	0,58
	c.f.m.	20
Max. pressure	bar	8
	p.s.i.	116
Nr. of stages	1	
Sound level (dB(A))	60	
Voltage / Frequency (Volt / Hz)	400/50	
Connection (G)	1/2"	
Controller	ETMII	
Type motor	Electric	
Energy efficiency	IE3	
Gross weight (kg)	205	
Net weight (kg)	178	
Packaging dimensions LxWxH (mm)	1540x620x1470	
Net Dimensions LxWxH (mm)	1430x550x1310	

\*Sound pressure level measurement carried out at a distance of 7 metres.  
FNA S.p.A. - Via Einaudi, 6 - 10070 Robassomero (TO) - Italy - [www.finicompressors.com](http://www.finicompressors.com) - [info@fnacompressors.com](mailto:info@fnacompressors.com)