

MICRO 5.5-10-270



Screw compressor with belt transmission, complete with tank.

Three-phase belt-transmission lubricated screw compressor with ETMII electronic controller and star/delta starter. Soundproof cab made of painted sheet metal and complete with 270-litre tank

TECHNICAL DATA

| | | |
|---------------------------------|----------------------|------|
| Product code | V91J092FNM701 | |
| Lubrication | Lubricated | |
| Air-end | FS14 | |
| Air receiver (l) | 270 | |
| Power | 5,5 | |
| Air outflow | l/min. | 650 |
| | m ³ /min. | 0,65 |
| | c.f.m. | 23 |
| Max. pressure | bar | 10 |
| | p.s.i. | 145 |
| Nr. of stages | 1 | |
| Sound level (dB(A)) | 64 | |
| Voltage / Frequency (Volt / Hz) | 400/50 | |
| Connection (G) | 1/2" | |
| Controller | ETMII | |
| Type motor | Electric | |
| Energy efficiency | IE3 | |
| Gross weight (kg) | 240 | |
| Net weight (kg) | 205 | |
| Packaging dimensions LxWxH (mm) | 1720x750x1680 | |
| Net Dimensions LxWxH (mm) | 1560x570x1390 | |

*Sound pressure level measurement carried out at a distance of 7 metres.