

MICRO 5.5-08-270 ES

Screw compressor with belt transmission, complete with tank and dryer.

Three-phase lubricated screw compressor with belt transmission, ETMII electronic controller and star/delta starter. Sheet metal soundproof cab complete with 270-litre tank and refrigerated dryer

\*Image is for illustrative purposes only



TECHNICAL DATA

Product code	V91JW92FNM801	
Lubrication	Lubricated	
Air-end	FS14	
Air receiver (l)	270	
Power	5,5	
Air outflow	l/min.	720
	m3/min.	0,72
	c.f.m.	25
Max. pressure	bar	8
	p.s.i.	116
Nr. of stages	1	
Sound level (dB(A))	64	
Voltage / Frequency (Volt / Hz)	400/50	
Connection (G)	1/2"	
Controller	ETMII	
Type motor	Electric	
Energy efficiency	IE3	
Gross weight (kg)	265	
Net weight (kg)	230	
Packaging dimensions LxWxH (mm)	1720x750x1680	
Net Dimensions LxWxH (mm)	1560x570x1390	

\*Sound pressure level measurement carried out at a distance of 7 metres.

FNA S.p.A. - Via Einaudi, 6 - 10070 Robassomero (TO) - Italy - [www.finicompressors.com](http://www.finicompressors.com) - [info@fnacompressors.com](mailto:info@fnacompressors.com)