

## PLUS 8-10-270 ES

Screw compressor with belt transmission, complete with tank and dryer.

Lubricated screw compressor with belt transmission, ETMII electronic controller. Soundproof cab in painted sheet metal, complete with 270-litre tank and refrigerated dryer



## TECHNICAL DATA \_\_\_\_\_

| Product code                    |         | V91NH92FNM801 |
|---------------------------------|---------|---------------|
| Lubrication                     |         | Lubricated    |
| Air-end                         |         | FS26          |
| Air receiver (I)                |         | 270           |
| Power                           |         | 7,5           |
| Air outflow                     | l/min.  | 1000          |
|                                 | m3/min. | 1,00          |
|                                 | c.f.m.  | 35            |
| Max. pressure                   | bar     | 10            |
|                                 | p.s.i.  | 145           |
| Nr. of stages                   |         | 1             |
| Sound level (dB(A))             |         | 68            |
| Voltage / Frequency (Volt / Hz) |         | 400/50        |
| Connection (G)                  |         | 1"            |
| Controller                      |         | ETMII         |
| Type motor                      |         | Electric      |
| Energy efficiency               |         | IE3           |
| Gross weight (kg)               |         | 345           |
| Net weight (kg)                 |         | 315           |
| Packaging dimensions LxWxH (mm) |         | 1720x750x1760 |
| Net Dimensions LxWxH (mm)       |         | 1560x680x1510 |

<sup>\*</sup>Sound pressure level measurement carried out at a distance of 7 metres.