

PLUS 15-10-500 ES

*Image is for illustrative purposes only

Screw compressor with belt transmission, complete with tank and dryer.

Lubricated screw compressor with belt transmission, ETMII electronic controller. Soundproof cab made of hot-painted sheet metal, complete with 500-litre tank and refrigerated dryer



TECHNICAL DATA

| | | |
|---------------------------------|---------------|------|
| Product code | V83NQ92FNM801 | |
| Lubrication | Lubricated | |
| Air-end | FS26 | |
| Air receiver (l) | 500 | |
| Power | 15 | |
| Air outflow | l/min. | 1850 |
| | m3/min. | 1,85 |
| | c.f.m. | 65 |
| Max. pressure | bar | 10 |
| | p.s.i. | 145 |
| Nr. of stages | 1 | |
| Sound level (dB(A)) | 70 | |
| Voltage / Frequency (Volt / Hz) | 400/50 | |
| Connection (G) | 1" | |
| Controller | ETMII | |
| Type motor | Electric | |
| Energy efficiency | IE3 | |
| Gross weight (kg) | 452 | |
| Net weight (kg) | 412 | |
| Packaging dimensions LxWxH (mm) | 2070x800x1850 | |
| Net Dimensions LxWxH (mm) | 2000x680x1630 | |