

K-MAX TS 90-07 VS

Highly efficient compressor with two-stage air-end, with direct drive transmission and inverter.

Two-stage lubricated screw compressor for maximum energy efficiency: coaxial transmission and inverter speed regulation. Modern and versatile LOGIN electronic controller.
Also available with integrated heat recovery exchanger.



TECHNICAL DATA

| | | |
|---------------------------------|--------------------|--------------|
| Product code | V60ZE97FNM045 | |
| Lubrication | Lubricated | |
| Power | 90 | |
| Air outflow | l/min. | 6303 - 19100 |
| | m3/min. | 6,30 - 19,10 |
| | c.f.m. | 223 - 675 |
| Max. pressure | bar | 8 |
| | p.s.i. | 116 |
| Nr. of stages | 2 | |
| Sound level (dB(A)) | 73 | |
| Voltage / Frequency (Volt / Hz) | 400/50 | |
| Connection (G) | DN50 | |
| Controller | Login | |
| Type motor | Electric | |
| Energy efficiency | IE4 | |
| Gross weight (kg) | 3500 | |
| Net weight (kg) | 3050 | |
| Packaging dimensions LxWxH (mm) | 3000 x 2000 x 2200 | |
| Net Dimensions LxWxH (mm) | 3000 x 2000 x 2200 | |

*Sound pressure level measurement carried out at a distance of 7 metres.