

K-MAX TS 110-07 VS

Highly efficient, two-stage screw compressor, with direct drive transmission and inverter.

Two-stage lubricated screw compressor for maximum energy efficiency: coaxial transmission and inverter speed regulation. Modern and versatile LOGIN electronic controller.

Also available with integrated heat recovery exchanger.



TECHNICAL DATA

|                                 |                    |              |
|---------------------------------|--------------------|--------------|
| Product code                    | V60ZH97FNM045      |              |
| Lubrication                     | Lubricated         |              |
| Power                           | 110                |              |
| Air outflow                     | l/min.             | 8217 - 24900 |
|                                 | m3/min.            | 8,22 - 24,90 |
|                                 | c.f.m.             | 290 - 879    |
| Max. pressure                   | bar                | 7            |
|                                 | p.s.i.             | 101          |
| Nr. of stages                   | 2                  |              |
| Sound level (dB(A))             | 76                 |              |
| Voltage / Frequency (Volt / Hz) | 400/50             |              |
| Connection (G)                  | DN80               |              |
| Controller                      | Login              |              |
| Type motor                      | Electric           |              |
| Energy efficiency               | IE4                |              |
| Gross weight (kg)               | 5300               |              |
| Net weight (kg)                 | 5100               |              |
| Packaging dimensions LxWxH (mm) | 3600 x 2000 x 2250 |              |
| Net Dimensions LxWxH (mm)       | 3600 x 2000 x 2250 |              |

\*Sound pressure level measurement carried out at a distance of 7 metres.